

REMARKS

The above amendments to the claims are requested in order to eliminate multiple claim dependency, thereby reducing the amount of the government filing fee.

If necessary to effect a timely response, this paper should be considered as a petition for an Extension of Time sufficient to effect a timely response, and please charge any deficiency in fees or credit any overpayments to Deposit Account No. 05-1323 (Docket #658/49679).

Respectfully submitted,

October 11, 2001



Donald D. Evenson
Registration No. 26,160

DDE:msy
CROWELL & MORING, LLP
P.O. Box 14300
Washington, DC 20044-4300
Telephone No.: (202) 628-8800
Facsimile No.: (202) 628-8844

VERSION WITH MARKINGS TO SHOW CHANGES MADE

In each claim appearing below, deletions are bracketed and additions are underlined.

3. (Amended) System according to [Claim 1 or 2] Claim 1, characterized in that the screw projects into the casing of the gear pump.

4. (Amended) System according to [one of Claims 1 to 3] Claim 1, characterized in that the filter is arranged between the gear pump and [the] a spraying head.

5. (Amended) System according to [one of Claims 1 to 4] Claim 1, characterized in that the screw casing has at least one conical part, and the screw has, in the area of the conical part, at least one tapering, and in that, for the controlled feeding of energy into the pumping medium, the screw is axially displaceable in the screw casing.

7. (Amended) System according to [Claim 5 or 6] Claim 5, characterized in that the tapering of the screw increases viewed in the delivery direction of the medium.

8. (Amended) System according to [one of Claims 5 to 7] Claim 5, characterized in that the screw has a double-helix-type construction.

9. (Amended) System according to [one of Claims 5 to 8] Claim 5, characterized in that a tangential plane on the screw in the area of the tapering encloses an angle of from 2 to 10°, preferably 8°, with the center axis of the screw.

10. (Amended) System according to [one of Claims 5 to 9] Claim 5, characterized in that the length of the screw is less than five times, preferably three times, the diameter of the screw.

11. (Amended) System according to [one of Claims 5 to 10] Claim 5, characterized in that the screw-type extruder has a cylindrical part in addition to the conical part.

13. (Amended) System according to [one of Claims 5 to 12] Claim 5, characterized in that the length of the cone is less than the diameter of the screw.

14. (Amended) System according to [one of the preceding claims] Claim 1, characterized in that the screw and/or the screw casing each have one hollow space respectively with at least two openings for admitting and discharging a temperature adjusting medium.

15. (Amended) Use of the system according to [one of Claims 1 to 14] Claim 1 for delivering elastomeric media, particularly caoutchouc.

16. (Amended) Method of operating the system according to [one of Claims 2 to 14] Claim 2, characterized in that, when a metal piece is detected, the delivery of the pumping medium is interrupted in that the drives of the screw and of the gear pump are stopped.

17. (Amended) Method of operating the system according to [one of Claims 2 to 14] Claim 2, characterized in that a detection of a metal piece is indicated to an operator who intervenes in the transport process of the pumping medium for removing the metal piece without requiring an interruption of the production process.